



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968
e-mail: info@s-line.it • www.s-line.it



MARKING TAPE

January 2019

Description:

Single sided PVC tape, 0.15 mm thickness, equipped with a natural rubber adhesive. Recommended for areas delimitation in warehouses, schools, gyms, track lanes, highlight machinery, equipment, etc.

Features and Applications:

- Excellent initial tack.
- Quick and easy to use.
- Excellent trampling resistance.
- Good resistance to aging, UV rays, detergents, oils and solvents.
- Good adhesion on irregular surfaces.
- Colors available: Yellow, Red, Green, Blue, White, Orange, White/Red and Yellow/Black.
- Recommended for areas delimitation.

TECHNICAL DATA SHEET

Thickness:	0.15 mm
Width available:	50 mm
Lengths available:	33 m
Product type:	Single sided Tape
Adhesive type:	Natural Rubber
Carrier type:	PVC
Peel adhesion on steel (PSTC1):	20 +/- 2 N/25mm
Elongation at break:	150%
Temperature resistance:	- 30° + 80°C
Application temperature:	Between 18°C and 35°C
Shelf life:	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.