



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
ph. +39 039 6011239 • fax +39 039 2124935 • P.IVA 06386430968
e-mail: info@s-line.it • www.s-line.it



CONFORMABLE

January 2019

Description:

Anti-slip tape composed by Aluminum backing coated with corundum fine mineral granules 60 grit, and modified acrylic solvent adhesive. The aluminum carrier, make this product able to adapt to the surfaces in a formidable way and it's suitable to make sure irregular surfaces and curves, such as knurled aluminum ladders, ramps, grids, etc. Recommended to indoor and outdoor applications, excellent resistance against trampling weathering, UV rays, oils, detergents and solvents. Available in rolls and die-cut strip form and in Black or Yellow colors. Apply to clean and dry surface.

TECHNICAL DATA SHEET

Adhesive:	Modified solvent acrylic
Carrier:	Aluminum carrier coated with corundum (60 grit)
Liner:	PET transparent film
Applied weight:	980 g/m ²
Roll ball test (PSTC6):	1 cm
Peel adhesion (PSTC1):	15 +/- 2 N/25mm
Static coefficient of friction:	Dry leather 1.11 Wet rubber 1.40
Dynamic coefficient of friction:	Dry leather 0.84 Wet rubber 1.12
Holding power:	≥ 48 hours
Temperature resistance:	- 30° + 90°C
Application temperature:	Between 18°C and 35°C
Shelf life:	12 months
Outdoor age resistance:	1-3 years under average walkway conditions

Ageing in following liquid immersion:

Water or detergents:	over 72 hours
Petrol or fuel:	over 72 hours
Diesel oil:	6 hours
Brake liquid:	10 hours
Engine oil:	30 hours
Bum test: 5,5" char at 1300°C for 4 minutes, will not sustain after flame is cut off.	

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.