



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968
e-mail: info@s-line.it • www.s-line.it

ISO 9001 ISO 14001



RESILIENT 40

January 2019

Description:

Anti-slip tape consisting of rubber embossed film 40 grit bonded to a polyester carrier with a modified solvent acrylic adhesive. Recommended for applications where barefoot walk is common or to shod the walkway like boats, swimming pools and sports areas. Also suitable for covering a cylinder in the textile sector. Available in rolls and die-cut strip form and in Black or Grey color. Apply to clean and dry surface.

TECHNICAL DATA SHEET

Adhesive:	Modified solvent acrylic
Carrier:	PET film coated with rubber particles (40 grit)
Liner:	White single sided PE coated paper
Applied weight:	980 g/m ²
Peel adhesion (PSTC1):	16 +/- 2 N/25mm
Static coefficient of friction:	Dry leather 1.11 Wet rubber 1.44
Dynamic coefficient of friction:	Dry leather 0.84 Wet rubber 1.12
Holding power:	≥ 48 hours
Temperature resistance:	- 30° + 110°C
Application temperature:	Between 18°C and 35°C
Shelf life:	12 months
Outdoor age resistance:	1-3 years under average walkway conditions

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.