



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy  
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968  
e-mail: info@s-line.it • www.s-line.it

ISO 9001 ISO 14001



## F-832

January 2019

### Description:

Double sided white polyethylene foam tape, 2.00 mm thickness, equipped with a solvent acrylic adhesive. Recommended for mounting different types of materials such as plates, panels, glass, metal, plastic profiles, wood, hooks, etc.

### Features and Applications:

- Excellent final adhesion.
- High thickness.
- Good resistance to aging, UV rays, temperatures, detergents, oils and solvents.
- Excellent adhesion on irregular surfaces.
- Recommended for mounting plates, panels, hooks, profiles of different materials such as metal, plastic, wood, glass, etc.

### TECHNICAL DATA SHEET

<b>Thickness:</b>	2.00 mm
<b>Width available:</b>	from 4 to 1,020 mm
<b>Lengths available:</b>	up to 150 m
<b>Product type:</b>	Double sided Tape
<b>Adhesive type:</b>	Solvent acrylic
<b>Carrier type:</b>	White polyethylene foam (PE)
<b>Density:</b>	67 kg/m <sup>3</sup>
<b>Liner type:</b>	Siliconized paper 110 gr/m <sup>2</sup>
<b>Liner color:</b>	White
<b>Peel adhesion on steel (PSTC1):</b>	16 +/- 2 N/25mm
<b>Static Shear:</b>	≥ 170 hours
<b>Rolling ball tack:</b>	< 10 cm
<b>Temperature resistance:</b>	- 30° + 100°C
<b>Application temperature:</b>	Between 18°C and 35°C
<b>Shelf life:</b>	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.