



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy  
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968  
e-mail: info@s-line.it • [www.s-line.it](http://www.s-line.it)



## S-961

January 2019

### Description:

Double sided transparent polyester tape, 0.08 mm thickness, equipped with a permanent/removable solvent acrylic adhesive. Recommended for general purpose applications, this tape is indispensable when it's necessary sticking temporarily different types of materials such as paper, cardboard, metal, glass, plastic, etc. without damaging surfaces.

### Features and Applications:

- Low thickness.
- Repositionable
- Clear removal.
- Good resistance to aging, UV rays, temperatures, detergents, oils and solvents.
- Good adhesion on smooth surfaces.
- Designed for temporary bonding of paper, cardboard, metal, plastic, glass, etc.

### TECHNICAL DATA SHEET

<b>Thickness:</b>	0.08 mm
<b>Width available:</b>	from 4 to 1,250 mm
<b>Lengths available:</b>	up to 1,000 m
<b>Product type:</b>	Double sided Tape
<b>Adhesive type:</b>	Permanent/Removable Solvent acrylic
<b>Carrier type:</b>	Polyester (PET)
<b>Carrier color:</b>	Transparent
<b>Liner type:</b>	Siliconized paper 110 gr/m2
<b>Liner color:</b>	Havana
<b>Peel adhesion on steel (PSTC1):</b>	Int. side 3 +/- 2 N/25mm
<b>Peel adhesion on steel (PSTC1):</b>	Ext. side 14 +/- 2 N/25mm
<b>Temperature resistance:</b>	- 30° + 150°C
<b>Application temperature:</b>	Between 18°C and 35°C
<b>Shelf life:</b>	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.