



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy  
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968  
e-mail: info@s-line.it • [www.s-line.it](http://www.s-line.it)



## S-973

January 2019

### Description:

Double sided black Non-woven tape, 0.12 mm thickness, equipped with a modified solvent acrylic adhesive. Recommended for paper industry applications, excellent adhesion on paper, cardboard, fabrics, samples, tissue, metal and treated plastics.

### Features and Applications:

- Low thickness.
- Excellent final adhesion.
- Excellent visibility.
- Good resistance to aging, UV rays, temperatures, detergents, oils and solvents.
- Excellent adhesion on irregular surfaces.
- Recommended for applications in the paper industry, samples, fabrics, tissue, cardboard, bricolage, splicing of papers, plastic etc.

### TECHNICAL DATA SHEET

|  |   |
|--|---|
| <b>Thickness:</b>                      | 0.12 mm                                 |
| <b>Width available:</b>                | from 4 to 1,250 mm                      |
| <b>Lengths available:</b>              | up to 1,000 m                           |
| <b>Product type:</b>                   | Double sided Tape                       |
| <b>Adhesive type:</b>                  | Modified solvent acrylic                |
| <b>Carrier type:</b>                   | Non-woven                               |
| <b>Carrier color:</b>                  | Black                                   |
| <b>Liner type:</b>                     | Siliconized paper 110 gr/m <sup>2</sup> |
| <b>Liner color:</b>                    | White                                   |
| <b>Peel adhesion on steel (PSTC1):</b> | 20 +/- 2 N/25mm                         |
| <b>Rolling ball tack:</b>              | < 10 cm                                 |
| <b>Temperature resistance:</b>         | - 40° + 150°C                           |
| <b>Application temperature:</b>        | Between 18°C and 35°C                   |
| <b>Shelf life:</b>                     | 12 months                               |

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.