



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy  
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968  
e-mail: info@s-line.it • [www.s-line.it](http://www.s-line.it)



## T-927 Transfer Tape

January 2019

### Description:

Permanent Transfer tape, 50 micron thickness, equipped with a modified solvent acrylic adhesive, reinforced with fibers and glass powders. This tape is indicated to bond different types of surfaces such as paper, cardboard, fabrics, leather, metal, plastic, etc.

### Features and Applications:

- Excellent final adhesion.
- Quick and easy to use.
- Good resistance to aging, UV rays, temperatures, plasticized, detergents, oils and solvents.
- Acid free.
- Paper industry, cardboard, exhibitors, pre-positioning of zip in leather field, photo album, etc.
- Also available in ATG format, 1" core, width 6-9-12-19 mm x 33 or 55 m

### TECHNICAL DATA SHEET

<b>Thickness:</b>	0.05 mm
<b>Width available:</b>	from 4 to 1,500 mm
<b>Lengths available:</b>	up to 800 m
<b>Product type:</b>	Transfer Tape
<b>Adhesive type:</b>	Permanent modified solvent acrylic
<b>Carrier type:</b>	Fiber and glass powders
<b>Liner type:</b>	Siliconized paper 90 gr/m <sup>2</sup>
<b>Liner color:</b>	Havana
<b>Peel adhesion on steel (PSTC1):</b>	18 +/- 2 N/25mm
<b>Static Shear:</b>	≥ 170 hours
<b>Rolling ball tack:</b>	< 10 cm
<b>Temperature resistance:</b>	- 30° + 150°C
<b>PH level:</b>	Between 7.0 and 8.5
<b>Shelf life:</b>	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.