

SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968 e-mail: info@s-line.it • **www.s-line.it**



AFB64 January 2019

Description:

Double-sided acrylic black foam tape, 0.64 mm thickness, equipped with an high performance solvent acrylic viscoelastic mass. This product replaces screws and rivets and is recommended for mounting permanently different types of materials such as glass, mirrors, metals, plastic profiles, wood, hooks, ceramic, etc..

Features and Applications:

- · Excellent final adhesion
- Replaces screws and rivets
- Excellent resistance to aging, UV rays, temperatures, plasticized, detergents, oils and solvents
- Good adhesion on treated plastic surfaces
- Excellent adhesion on irregular surfaces
- Ideal for vertical applications
- Recommended for mounting plates, panels, hooks, profiles of different materials such as metal, plastic, wood, glass, ceramic, automotive industry, constructions, etc..

TECHNICAL DATA SHEET

Thickness: 0.64 mm

Width available: from 4 to 830 mm

Lengths available: up to 33 m

Product type: Double-sided tape

Adhesive type: High performance solvent acrylic

Carrier type: Acrylic viscoelastic mass

Density: 800 +/- 100 kg/m3

Carrier color: Black

Liner type: 80 micron plastic film

Liner color: Red

Peel adhesion on steel (PSTC1): 28 +/- 2 N/25mm

Static Shear: > 183 hours (1,000g, will hold 11,000 minutes at 20°C)

Temperature resistance: - 30° + 150°C

Application temperature: Between 18°C and 35°C

Shelf life: 12 months