



SL srl • www.s-line.it

Via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
Ph. +39 039 6011239 • Fax +39 039 2124935 • E-mail: info@s-line.it
P.IVA 06386430968 • Codice SDI: USAL8PV

ISO 9001 ISO 14001



NGT200

January 2025

Description:

Double sided transparent acrylic foam tape, 2.00 mm thickness, equipped with a solvent acrylic viscoelastic adhesive mass. This product is recommended to bonding temporarily different types of materials such as glass, plastic, wood, hooks, metal, fabrics etc.

Features and applications:

- *High thickness.*
- *Excellent transparency.*
- *Excellent final adhesion.*
- *Quick and easy to use.*
- *Excellent resistance to aging, UV rays, temperatures, detergents, oils and solvents.*
- *Washable and reusable.*
- *Excellent adhesion on irregular surfaces.*
- *Repositionable.*
- *Suitable for mounting plates, panels, hooks, glass, wood, metal, plastic, fabrics, to fix carpets.*

Technical data sheet:

Thickness	2.00 mm
Width available	From 4 to 800 mm
Lengths available	Up to 100 m

Product type	Double sided tape
Adhesive type	Acrylic solvent
Carrier type	Acrylic viscoelastic mass
Carrier color	Transparent
Density	800 +/- 100 kg/m ³
Liner type	Plastic film 120gr/m ²
Liner color	Transparent

Peel adhesion on steel (PSTC1)	15 +/- 2 N/25 mm
Static shear	≥ 183 hours (1,000 g, will hold 11,000 minutes at 20°C)
Temperature resistance	-30° + 120°C
Application temperature	Between 18°C and 35°C
Shelf life	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.