



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy  
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968  
e-mail: info@s-line.it • [www.s-line.it](http://www.s-line.it)



## NSAE

April 2020

### General Description:

R13 certified printable adhesive corundum abrasive film, 60 grit thickness, coated with a special high-performance acrylic adhesive that ensures an excellent adhesion on walkways, sidewalks, steps and critical surfaces such as asphalt and concrete. This product guarantees an excellent grip even in wet conditions and is used for personalized printing signs for internal and external floors. Excellent resistance to footfall, temperatures, atmospheric agents, UV rays, oils, detergents and solvents.

### Characteristics and Applications:

- Excellent adhesion on difficult surfaces such as asphalt and concrete
- R13 anti-slip Certification (TEST DIN 51130:2014)
- Excellent resistance to detergents, solvents, aging and UV ray
- Excellent grip even in wet conditions
- Acid free
- For interior and exteriors floors
- Excellent resistance to footfall
- Ideal for horizontal applications on external floors such as entry, parking space, sidewalks, walkways and steps of subways, hospitals, schools, shopping centers, sports centers, offices, etc.

### TECHNICAL DATA

|                                       |                             |
|---------------------------------------|-----------------------------|
| <b>Product:</b>                       | Mono-adhesive tape          |
| <b>Adhesive type:</b>                 | High performance acrylic    |
| <b>Backing type:</b>                  | Corundum abrasive particles |
| <b>Thickness:</b>                     | 60 grit                     |
| <b>Anti-slip properties:</b>          | R13 (Test DIN 51130:2014)   |
| <b>Maximum holding power:</b>         | ≥ 4 hours                   |
| <b>Waterproofing:</b>                 | 12 months                   |
| <b>Ideal application temperature:</b> | from + 15° to + 35°C        |
| <b>Resistance to temperature:</b>     | from - 30° to + 100°C       |
| <b>Shelf life:</b>                    | 12 months                   |

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The end-user should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.