

SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968 e-mail: info@s-line.it • www.s-line.it



NSAV April 2020

General information:

Mono-adhesive PVC tape of 100 micron thickness, coated with a solvent free, age-resistant and permanent elastic acrylate adhesive "dot-shaped" that guarantees an easy, fast, bubble-free and repositionable application. Product used for the creation of personalized adhesive signs for interior and exterior spaces.

Characteristics and Applications:

- NSAV is especially indicated for vertical surfaces
- Excellent adhesion on multiple surfaces such as glass, wood, aluminum, steel, plastic, etc.
- Bubble-free
- Easy and quick to use
- Repositionable
- Does not damage surfaces
- Acid free
- Solvent free
- Excellent resistance to aging and UV rays
- For interior and exterior spaces
- Ideal for vertical applications on doors, panels, windows, glazings, partitions, etc.

TECHNICAL DATA

Thickness: 0.10 mm

Product: Mono-adhesive tape

Adhesive type:Polyacrylate dispersion dotsBacking type:Polyvinyl chloride(PVC)

Adhesive strenght after 24h: > 1.5 N/25mm (AFERA 4001)

Elongation at tear: > 150% (DIN EN ISO 527-3 50mm/min) **Tear resistance:** > 30 N/mm (DIN EN ISO 527-3 50mm/min)

pH-value: 7.0

Ideal application temperature: from + 18° to + 25°C

Resistance to temperature: from -30° to $+50^{\circ}$ C for long periods $/+70^{\circ}$ C for short periods

Shelf life: 12 months