



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
ph. +39 039 6011239 • fax+39 039 2124935 • P.IVA 06386430968
e-mail: info@s-line.it • www.s-line.it

ISO 9001 ISO 14001



S710

January 2019

Description:

Double-sided non-woven tape, 0.10 mm thickness, equipped with a synthetic rubber adhesive. Recommended for general purpose applications, good initial tack and adhesion on paper, cardboard, fabrics, samples, tissue.

Features and Applications:

- Low thickness
- Good initial tack
- Excellent adhesion on irregular surfaces
- Recommended for applications in the paper industry, samples, fabrics, tissue, cardboard, bricolage, foam, etc..

TECHNICAL DATA SHEET

Thickness:	0.10 mm
Width available:	from 4 to 1,020 mm
Lengths available:	up to 1,000 m
Product type:	Double-sided tape
Adhesive type:	Synthetic rubber
Carrier type:	Non-woven
Carrier color:	Neutral
Liner type:	Siliconized paper 110 gr/m ²
Liner color:	Yellow
Peel adhesion on steel (PSTC1):	22 +/- 2 N/25mm
Rolling ball tack:	< 10 cm
Temperature resistance:	- 30° + 70°C
Application temperature:	Between 18°C and 35°C
Shelf life:	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.