



SL srl • www.s-line.it

Via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
Ph. +39 039 6011239 • Fax +39 039 2124935 • E-mail: info@s-line.it
P.IVA 06386430968 • Codice SDI: USAL8PV

ISO 9001 ISO 14001



S760

June 2025

Description:

Permanent transfer tape reinforced with a PET mesh, 0.16 mm thickness, equipped with a solvent acrylic adhesive. This tape is suitable to bonding and laminating foam materials, to fix and mounting different types of surfaces such as fabrics, wood, metal, plastic.

Features and applications:

- *Excellent final adhesion.*
- *Excellent conformability on irregular surfaces.*
- *Excellent resistance to aging, UV rays, temperatures, detergents, oils and solvents.*
- *Recommended to bonding and laminating foam materials, for mounting plates, panels, profiles of different materials such as wood, metal, plastic, fabrics.*

Technical data sheet:

Thickness	0.16 mm
Width available	From 4 to 1,020 mm
Lengths available	Up to 1,000 m

Product type	Double sided tape
Adhesive type	Solvent acrylic
Carrier type	PET mesh
Liner type	Siliconized paper 110 gr/m ²
Liner color	Avana

Peel adhesion on steel (PSTC1)	15 +/- 2 N/25 mm
Static shear	≥ 170 hours
Rolling ball tack	< 10 cm
Temperature resistance	-30° + 120°C
Temperature resistance	Between 18°C and 35°C
Shelf life	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.