



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
ph. +39 039 6011239 • fax +39 039 2124935 • P.IVA 06386430968
e-mail: info@s-line.it • www.s-line.it

ISO 9001 ISO 14001



S979

January 2019

Description:

Double-sided white PVC tape, 0.22 mm thickness, equipped with high performance modified solvent acrylic adhesive. Recommended for mounting different surfaces such as cardboard, glass, metal, rubber, plastic profiles.

Features and Applications:

- White covering
- Excellent final adhesion
- Excellent resistance to aging, UV rays, detergents, oils and solvents
- Excellent adhesion on plastics surfaces
- Recommended for mounting different types of surfaces, cardboard, metal, glass, plastic profiles, foam, panels, display etc..

TECHNICAL DATA SHEET

Thickness:	0.20 mm
Width available:	from 4 to 1,250 mm
Lengths available:	up to 500 m
Product type:	Double-sided tape
Adhesive type:	Modified solvent acrylic
Carrier type:	PVC
Carrier color:	White
Liner type:	Siliconized paper 110gr/m ²
Liner color:	Havana
Peel adhesion on steel (PSTC1):	22 +/- 2 N/25mm
Static Shear:	≥ 170 hours
Rolling ball tack:	< 10 cm
Temperature resistance:	- 30° + 80°C
Application temperature:	Between 18°C and 35°C
Shelf life:	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.