



SL srl - via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
ph. +39 039 6011239 • fax +39 039 2124935 • P.IVA 06386430968
e-mail: info@s-line.it • www.s-line.it

ISO 9001 ISO 14001



T922 Transfer Tape

January 2019

Description:

Permanent Transfer tape, 30 micron thickness, equipped with solvent acrylic adhesive, reinforced with fibers and glass powders. This tape is indicated to bond different types of surfaces such as paper, cardboard, fabrics, leather, metal, plastic, etc..

Features and Applications:

- Good final adhesion
- Quick and easy to use
- Good resistance to aging, UV rays, temperatures, detergents, oils and solvents
- Acid free
- Paper industry, cardboard, exhibitors, pre-positioning of zip in leather field, photo album, etc..
- Also available in ATG format, 1" core, width 6 – 9 – 12 – 19 mm x 55 m

TECHNICAL DATA SHEET

Thickness:	0.03 mm
Width available:	from 4 to 1,500 mm
Lengths available:	up to 800 m
Product type:	Transfer Tape
Adhesive type:	Permanent solvent acrylic
Carrier type:	Fiber and glass powders
Liner type:	Siliconized paper 65 gr/m ²
Liner color:	White
Peel adhesion on steel (PSTC1):	15 +/- 2 N/25mm
Static Shear:	≥ 170 hours
Rolling ball tack:	< 10 cm
Temperature resistance:	- 30° + 180°C
PH level:	Between 7.0 and 8.5
Shelf life:	12 months

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.